












CROSS TABLES				
	T0100	T0200	T0201	T0300
Nº of axes	3	2	3	2
size (h) mm	210x170x60	490x453x99	490x453x10	570x529x105
weight	4 kg	24 kg	33 kg	39 kg
compatible printers	100, 125, 125R, 150, 200, 250, mi.micro, micro LP, micro	100, 125, 125R, 150, 200, 250, micro LP	100, 125, 125R, 150, 200, 250, micro LP	100, 125, 125R, 150, 200, 250, micro LP

ROTARY TABLES					
	TRCN02	TRCN03	TRCN04	TRCN06	TRCN10
drive	electronic	electronic	electronic	electronic	electronic
max. disc diameter	da 350 a 1000mm	da 350 a 1000mm	da 350 a 1000mm	da 350 a 1000mm	da 350 a 1000mm
Nº of fixtures	programmable	programmable	programmable	programmable	programmable
positioning repetivity	+/- 1´	+/- 1´	+/- 1´	+/- 1´	+/- 1´
compatible printers	100, 125, 08, mi.micro, micro	100, 125, 125R, 150, 200, 250, 08, mi.micro, micro LP, micro	100, 125, 125R, 150, 200, 250, 08, mi.micro, micro LP, micro	125R, 150, 200, 250, mi.micro, micro LP, micro	150, 200, 250, 08, micro LP, micro

OVAL FLAT CONVEYORS				
	MEG9		MEG12	
Nº of fixtures	9		12	
pitch	152.4 mm (6")		114.3 mm (4,5")	
positioning repetivity	+/- 0.01 mm		+/- 0.01 mm	
size	1000x450x200 mm		1000x450x200 mm	
weight	125 kg		135 kg	
compatible printers	125, 125R, 150, 200, 250		125, 125R, 150, 200, 250	

INDEXERS								
	PS460		PR610		PRP610		ER900	
total stroke	460 mm		610 mm		610 mm		990 mm	
positioning repetivity	+/- 0.01 mm		+/- 0.01 mm		+/- 0.01 mm		+/- 0.01 mm	
size	985x205x178 (h) mm		1115x275x200 (h) mm		1115x470x350 (h) mm		1700x450x270 (h) mm	
weight	30 kg		50 kg		75 kg		310 kg	
compatible printers	125, 125R, 150, 200, 250		150, 200, 250		150, 200, 250		200, 250	

LINEAR CONVEYORS



MEM18

MEM24

MEM32

	MEM18	MEM24	MEM32
Nº of fixtures	18	24	32
pitch	152.4 mm (6")	152.4 mm (6")	152.4 mm (6")
positioning repetitivity	+/- 0.01 mm	+/- 0.01 mm	+/- 0.01 mm
length with safety guarding	2100 mm	2500 mm	3100 mm
compatible printers	150, 200, 250	150, 200, 250	150, 200, 250



MEG30'24

MEG30'32

	MEG30'24	MEG30'32
Nº of fixtures	24	32
pitch	152.4 mm (6")	152.4 mm (6")
positioning repetitivity	+/- 0.01 mm	+/- 0.01 mm
length with safety guarding	2700 mm	3300 mm
compatible printers	200, 250	200, 250