

LOGICA 05.5

Numerically controlled pad printing centre for multicolour printing

Up to 6 movement axis easily programming

Fully electrical operation

Available in 3 versions different for printing force and speed

CHARACTERISTICS

- All the mechanical movements are motorized via numerical control and lead screw, guarantee high precision and smooth working.
- Manufactured from light alloy and special steel. The simple and robust construction was also conceived to guarantee a long life of working without maintenance.
- The computerized numerical control ensures complete flexibility of operation and simplicity without compromise.
- Setting up adjustments can be carried out via the numeric keyboard with alphanumeric display. Ability to freely position the keyboard, where most comfortable for the user.
- Memory of all different work programs for easy changeover set up.
- Automatic colours registering on x y r axes, for immediate start-up (optional).
- Ability to print under the printing plate, allowing decoration in every position on the large sized objects.
- Ability to print on different surface levels of the same object, adjusting easily the stroke through the keyboard.
- Low power consumption, economical since compressed air is not required. It's exclusive electric operation presents a considerable advantage compared to an equivalent pneumatic machine, a saving of more than 15.000 - 20.000 kw/h in a year can be achieved assuming one working shift per day.
- Eco-friendly. Due to its available hermetic ink system preventing solvent evaporation.
- Changeover time reduced to a few minutes, thanks to the considerations given in the design concept to apply ergonomic principles to the system.
- Ergonomic design to easy access all mechanical parts.
- Accurate movement of the support slide-table with adjustable height.



Logica 05.5 2 colours with indexer Mod. PRN990, cross table Mod. TO200, 4° rotary axes and safety guarding

Models	Max dia. ink cup
LOGICA 05.5 (printing force 4000 N)	n. 4 dia. 160 mm n. 5 dia. 130 mm n. 2 oval 350 / 115 mm n. 3 oval 225 / 110 mm or mixed
LOGICA 05.5 S (printing force 5000 N)	n. 3 dia. 195 mm n. 4 dia. 160 mm. n. 5 dia. 130 mm n. 6 dia. 115 mm n. 2 oval 350 / 115 mm n. 3 oval 225 / 110 mm or mixed
LOGICA 05.5 SV (printing force 4000 N)	Place the same amount and size cup of mod. Logica 05.5 S but with a higher printing speed.



LOGICA 05.5

SERIE LOGICA FLESSIBILE

DATI TECNICI

- Operation: **electric with numerical control**
- Printing force mod. Logica 05.5 and 05.5 SV: **4000 N**
- Printing force mod. Logica 05.5 S: **5000 N**
- Max printing speed mod. Logica 05.5 and 05.5 S: **regolabile fino a 1200 c/h (*)**
- Max printing speed mod. Logica 05.5 SV: **adjustable up to 1700 c/h (*)**
- Number of colours: **1 - 2 - 3 - 4 - 5 - 6**
- Maximum dia. ink cup: **195 mm** mod. Logica 05.5 S and 05.5 SV
160 mm mod. Logica 05.5
- X axes pad register: **+/- 20 mm**
- Vertical stroke: **180 mm**
- Maximum pad height: **220 mm**
- AC supply: **380 V - triple phase - 50/60 Hz**
- Average consumption: **about 1500 W**
- Weight with indexer and safety guarding: **about 1300 Kg**
- Sizes with indexer and safety guarding: **about 2550 x 1600 x 2250 (h) mm**

(*) The above mentioned printing speed is the max achievable and will reduce when the vertical pad stroke is increased or when delay times have been programmed into the cycle. The maximum printing speed also depends on the parts loading device.

STANDARD PACKAGES

To make the choice easier, Tosh proposes a series of standard packages, between the machine and the conveying systems, that suits your specific application.

Among the suggested and more popular, there are:


- **Cross Table** in different dimensions
- Numerically controlled **indexers** with programmable and adjustable pitch and **automatic pad cleaning**
- Fully electric **Oval flat conveyors**
- Electromechanical numerically controlled **rotary tables**
- Fully electric **rectilinear tracked conveyors**
- Fully electric **rectilinear inclined conveyors**
- **Pre-treatment devices** (flame or corona treatment)
- **Drying devices** (air, U.V. and I.R.)
- Modular **pad pre-drying devices**

On the cover a standard package example of:

Logica 05.5 2 colours with indexer Mod. PRN 990, cross table Mod. TO200, 4° rotary axes and safety guarding.

OPTIONAL

Cross tables



Recommended for applications where there is a single fixture, they allow rapid alignment on more axis of the part to the print.

Indexers



Single fixture linear transfers for multicolour printing on medium and large products.

Oval flat conveyors



Multifixture linear transfers for multicolour printing on small and medium products or used for additional in-line processes

Rotary tables



Recommended for multicolour printing or when high production cadences are required. They can also be used for additional in-line processes.

Rectilinear tracked conveyor



Linear transfer with horizontal rotation axes, available in various dimensions. RECOMMENDED in standard configuration, for multi-colours with extra fixtures, for additional functions such as: pre and post treatment, loading and unloading products or when more than one machine is used on line.

Rectilinear inclined conveyor



Linear transfer with inclined working planes is also suitable for use fixtures which, as in the tracked conveyor, run below the printing plane i. e. under the table. Also usable as the oval, flat conveyor, type MEG, but with higher number of fixtures and available in various dimensions. RECOMMENDED for multi-colours printing with additional functions to the printing phase, or for multi-stage loading.

Doctoring refresher devices



Ideal for printing large images that don't fit into ink cup size.

BECAUSE OF CONTINUOUS IMPROVEMENT, WE RESERVE THE RIGHT TO CHANGE SPECIFICATION, DESIGN MATERIALS WITHOUT NOTICE.

TOSH®

MACCHINE E SERVIZI
PER LA STAMPA SU OGGETTI



TOSH S.r.l. - Via Lambro 84, I - 20089 Quinto Stampi Rozzano (MI)
Tel. +39 02 57566.1 (10 linee r.a.) - Fax +39 02 89200266
E-mail: info@tosh.it www.tosh.it